

Ícaro Lineal

Placa de techo lineal de alto rendimiento con CRI 85. U.G.R. < 19.

Marco de aluminio anodizado.

Ceiling lighting line high efficiency with CRI 85. U.G.R. < 19.

Profile aluminium anodized.

ACABADO / FINISHES:

Posibilidad de lacar marco según RAL, consultar cantidad mínima.

Possibility RAL lacquer frame, refer minimum.

MEDIDAS / MEASUREMENTS:

1200x150mm



TRAMO INICIAL / FINAL	REF.	N.LEDS	COLOR	LIGHT FLOW	DRIVER	ALIM./POWER	W	IP
	ICAL-121-F15	96	5.000°K	2.309 Lm	NO REG.	115-305Vac	26W	IP30
	ICAL-121-F14	96	4.000°K	2.199 Lm	NO REG.	115-305Vac	26W	IP30
	ICAL-121-R15	96	5.000°K	2.309 Lm	REG. 1-10V	115-305Vac	26W	IP30
	ICAL-121-R14	96	4.000°K	2.199 Lm	REG. 1-10V	115-305Vac	26W	IP30
	ICAL-121-D15	96	5.000°K	2.309 Lm	DALI	115-305Vac	26W	IP30
	ICAL-121-D14	96	4.000°K	2.199 Lm	DALI	115-305Vac	26W	IP30
	ICAL-141-F15	192	5.000°K	4.622 Lm	NO REG.	115-305Vac	52W	IP30
	ICAL-141-F14	192	4.000°K	4.421 Lm	NO REG.	115-305Vac	52W	IP30
	ICAL-141-R15	192	5.000°K	4.622 Lm	REG. 1-10V	115-305Vac	52W	IP30
	ICAL-141-R14	192	4.000°K	4.421 Lm	REG. 1-10V	115-305Vac	52W	IP30
	ICAL-141-D15	192	5.000°K	4.622 Lm	DALI	115-305Vac	52W	IP30
	ICAL-141-D14	192	4.000°K	4.421 Lm	DALI	115-305Vac	52W	IP30

TRAMO CENTRAL	REF.	N.LEDS	COLOR	LIGHT FLOW	DRIVER	ALIM./POWER	W	IP
	ICAL-221-F15	96	5.000°K	2.309 Lm	NO REG.	115-305Vac	26W	IP30
	ICAL-221-F14	96	4.000°K	2.199 Lm	NO REG.	115-305Vac	26W	IP30
	ICAL-221-R15	96	5.000°K	2.309 Lm	REG. 1-10V	115-305Vac	26W	IP30
	ICAL-221-R14	96	4.000°K	2.199 Lm	REG. 1-10V	115-305Vac	26W	IP30
	ICAL-221-D15	96	5.000°K	2.309 Lm	DALI	115-305Vac	26W	IP30
	ICAL-221-D14	96	4.000°K	2.199 Lm	DALI	115-305Vac	26W	IP30
	ICAL-241-F15	192	5.000°K	4.622 Lm	NO REG.	115-305Vac	52W	IP30
	ICAL-241-F14	192	4.000°K	4.421 Lm	NO REG.	115-305Vac	52W	IP30
	ICAL-241-R15	192	5.000°K	4.622 Lm	REG. 1-10V	115-305Vac	52W	IP30
	ICAL-241-R14	192	4.000°K	4.421 Lm	REG. 1-10V	115-305Vac	52W	IP30
	ICAL-241-D15	192	5.000°K	4.622 Lm	DALI	115-305Vac	52W	IP30
	ICAL-241-D14	192	4.000°K	4.421 Lm	DALI	115-305Vac	52W	IP30

KIT DE SUSPENSION PARA ICARO LINEAL / SUSPENSION KIT FOR ICARO LINEAL

REF.	COMPOSICION KIT / KIT QUANTITY	MEDIDA CABLE / CABLE MEAS.
ICAL-KIT-001	6 CABLES / 6 GANCHOS NIQUEL/ 1 UNION	2000x1.2mm (NECESARIO)
ICAL-KIT-002	2 CABLES / 2 GANCHOS NIQUEL/ 1 UNION	2000x1.2mm (AMPLIACION TRAMO)



NORMATIVA / STANDARD

MATERIALES / COMPONENTS	FUENTE ALIMENTACION / POWER SUPPLY
PMMA: DIN 53436 / PET: DIN 40634 ISO 7724	EN 51015, EN 61000-2-3, EN 61000-3-3, EN 55024
PC: EN 13501-1 / ALU: EN 10204 EN 755-2 UNE-EN 573/3	EN 61000-4-2,3,4,5,6,8,11 EN 61547, CE

OBSERVACIONES / NOTES

Fuente de alimentación incluida. PC: Norma fuego B-s1-d0
Power supply included. PC: Fire standard B-s1-d0